



Weight: 8.24 g

Body

Coupling Nut

Suitable Cables: Semi-rigid.141

Brass

Brass

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

Tin-Zinc-Copper-Alloy 100 Over Copper 50

Tin-Zinc-Copper-Alloy 100 Over Copper 50



CABLE ASSEMBLY INSTRUCTION BNC3300-0141 JYE BAO CO., LTD. Α В · D **CONTACT PIN BODY DIAGRAM** ASSEMBLY INSTRUCTION Step 1: STRIP AS SHOWN. 4.2 [.165] Step 2: PUT 0.29 MM GAGE IN PLACE, INSERT CABLE'S CENTER CONDUCTOR INTO CENTER PIN AND SOLDER IN 'Y'. GAGE 0.29MM Step 3: INSERT PREPARED CABLE INTO CONNECTOR BODY "B" AND USE SOLDERING FIXTURE ST-010 "ST-008", INSERT TOOL "ST-010" AND LOCATOR TOOL "ST-011" TO FIX THE CONNECTOR. SOLDER IN "X". ST-011

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.