





Parts	Material	Plating (Micro-inch)
Ferrule	Brass	Gold 4 Over Nickel-Phosphorus 80 Over Copper 20
Barrel	Brass	Gold 4 Over Nickel-Phosphorus 80 Over Copper 20
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus 80 Over Copper 20
Insulator	Teflon	
Body	Brass	Gold 4 Over Nickel-Phosphorus 80 Over Copper 20

Weight:

Suitable Cables: JBY300,5DFB

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



## CABLE ASSEMBLY INSTRUCTION JYE BAO CO., LTD. SMA8100-L300 **TAIPEI TAIWAN R.O.C** Α В С **BODY CONTACT PIN FERRULE** ASSEMBLY INSTRUCTION **DIAGRAM** Step 1: STRIP AS SHOWN. 5.4 [.213] Step 2: SLIDE FERRULE " C " OVER CABLE. Step 3: PUT PIN " B " ON CENTER CONDUCTOR AND SOLDER IN " Y ". С **▽** = Step 4: LOOSEN BRAIDING AND SLIDE CONNECTOR "A" IN PLACE. Step 5: SLIDE FERRULE " C " TOWARDS THE CONNECTOR " A " AND CRIMP.

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.