



● Slider Controls





● Tuning knob controls

Remotely Control Icom Transceivers through an IP Network

- The RS-BA1 allows you to use the transceiver installed in another room or even from a remote location over the Internet.
- Low latency, high quality audio over an IP network.
- Most functions and modes of your transceiver, including interference rejection functions and IF filter settings, can be controlled using CI-V commands.
- Remote power ON/OFF function wakes up certain transceivers from the standby mode.

Advanced Remote Control Interface Tailored to Icom Transceivers

- Slider control or tuning knob control screens are selectable for RF power, CW pitch, RF gain, and SQL and AF level.
- The spectrum scope with the waterfall function can be observed on the RS-BA1. (For a single band only the IC-7851, 7850 and 7300)
- Rx Voice recording function.
- Optional RC-28 USB remote encoder provides a hardware dial/transmit function for realistic dial operation.



● Spectrum scope with waterfall (only for IC-7851/7850/7300)

Functions Compatibility Chart

	IC-7851 IC-7850	IC-7800 IC-7700	IC-7600	IC-7410 IC-9100	IC-7300	IC-7200	IC-7100
Server Function	✓	✓	–	–	–	–	–
Remote Power ON/OFF	✓	✓	✓	–	✓	–	✓
Spectrum Waterfall Scope	✓	–	–	–	✓	–	–
APF AF Level Adjustment	✓	✓	✓	–	–	–	–
CW Keyer	✓	✓	✓	✓	✓	–	✓
Voice Recording/Playback	✓	✓	✓	✓	✓	✓	✓
USB Dial with Optional RC-28	✓	✓	✓	✓	✓	✓	✓

* Depending on your transceiver, some functions or modes cannot be used, or you need to update the transceiver's firmware. Please use the latest firmware version of the transceiver.

MINIMUM SYSTEM REQUIREMENTS

PC (Base server station or Remote station)

- Operating system: Windows® 10 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), (Except for Windows® RT), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit)
 - CPU: 1GHz Processor or better (A multicore CPU recommended)
 - Memory: Windows® 7/8.1/10: 1GB (32-bit) or 2GB (64-bit) Windows Vista®: 1GB (32-bit/64-bit)
 - Hard disk space: 70MB of available disk space or more (The Voice Memory function or Recording function will require more)
 - Display resolution: 1024x600 pixels or more
 - Other: IP network capability, CD/DVD drive for the program installation
- Base server station USB 1.1, 2.0 or 3.0 port
Remote station Speaker and microphone or headset (purchase separately)
On-board sound chipset recommended
- Network data speed:
 - Base server station Upload: 500 kbps Download: 350 kbps or faster
 - Remote station Upload: 350 kbps Download: 500 kbps or faster (When the default audio quality is used)

OPTIONS

RC-28 USB Remote Encoder



- Adjustable dial sensitivity and auto tuning step (OFF/Low/High)
- Two programmable keys of four functions (Push/Hold down)
- Large PTT switch (Push to toggle/Hold down to transmit)
- The RC-28 will still operate in the background even if a different application (Such as logging software) is open

RS-BA1 SUPPLIED ITEMS

- CD (including the RS-BA1 instruction manual, the RS-BA1 installer, the USB driver and the USB driver installation guide)
- USB cable (A-B type) • Installation guides

The latest software updater can be downloaded free from: <http://www.icom.co.jp/world/support/index.html>

All stated features, screen shots, and specifications may be subject to change without notice or obligation. Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Icom Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 www.icom.co.jp/world

Count on us!

Icom America Inc.
12421 Willows Road NE,
Kirkland, WA 98034, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom (Europe) GmbH
Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-50
E-mail: info@icom-europe.com
URL: <http://www.icomeurope.com>

Icom France s.a.s.
Zac de la Plaine,
1 Rue Brindejonn des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada
Glenwood Centre #150-6165
Highway 17A, Delta, B.C.,
V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Spain S.L.
Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom (Australia) Pty. Ltd.
Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Shanghai Icom Ltd.
No.101, Building 9, Caifuxingyuan Park,
No.188 Maoting Road, Chedun Town,
Songjiang District, Shanghai, 201611, China
Phone: +86 (021) 6153 2768
Fax: +86 (021) 5765 9987
E-mail: bjicom@bjicom.com
URL: <http://www.bjicom.com>

Icom Brazil
Rua Itororó, 444 Padre Eustáquio
Belo Horizonte MG,
CEP: 30720-450, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
Blacksale House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone: +44 (0) 1227 741741
Fax: +44 (0) 1227 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom New Zealand
39C Rennie Drive, Airport Oaks,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>