

NEXEDGE KTI-3

NETWORK INTERFACE UNIT

INTERFACE RESEAU

MODE D'EMPLOI

UNIDAD INTERFAZ DE RED
MANUAL DE INSTRUCCIONES

UNITA' INTERFACCIA DI RETE MANUALE DI ISTRUZIONI

NETZWERK INERFACE BOX
BEDIENUNGSANLEITUNG

NETWERK KOPPELING
GEBRUIKSAANWIJZING

AĞ ARAYÜZ BİRİMİ KULLANIM KILAVUZU

ΜΟΝΑΔΑ ΔΙΑΣΥΝΔΕΣΗΣ ΔΙΚΤΥΟΥ ΟΔΗΓΙΕΣ ΧΡΗΣΗΣ

СЕТЕВОЕ ИНТЕРФЕЙСНОЕ УСТРОЙСТВО РУКОВОДСТВО ПОЛЬЗОВАТЕЛЯ

JVC KENWOOD Corporation

© B62-2283-20 (M) 09 08 07 06 05 04 03 02

One or more of the following statements may be applicable:

FCC WARNING

This equipment generates or uses radio frequency energy. Changes or modifications to this equipment may cause harmful interference unless the modifications are expressly approved in the instruction manual. The user could lose the authority to operate this equipment if an unauthorized change or modification is made.

INFORMATION TO THE DIGITAL DEVICE USER REQUIRED BY THE FCC

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can generate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that the interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer for technical assistance.

THANK YOU

We are grateful you purchased this **Kenwood** network interface unit. You can implement a Conventional network by using this product in combination with a NEXEDGE Repeater.

PRECAUTIONS

- Do not expose the unit to rain or moisture; to prevent fire or electric shock.
- Do not open the unit under any circumstances; to avoid risk of electric shock.
- Do not expose the unit to long periods of direct sunlight, nor place it close to heating appliances.
- Do not place the unit in excessively dusty and/or humid areas, nor on unstable surfaces.
- If you detect an abnormal odor or smoke coming from the unit, disconnect the power from the unit immediately. Contact your **Kenwood** service center or dealer.

Information on Disposal of Old Electrical and Electronic Equipment (applicable for EU countries that have adopted separate waste collection systems)



Products with the symbol (crossed-out wheeled bin) cannot be disposed as household waste.

Old electrical and electronic equipment should be recycled at a facility capable of handling these items and their waste byproducts. Contact your local authority for details in locating a recycle facility nearest to you. Proper recycling and waste disposal will help conserve resources whilst preventing detrimental effects on our health and the environment.

UNPACKING AND CHECKING EQUIPMENT


Note: The following unpacking information is for use by your **Kenwood** dealer, an authorized **Kenwood** service center, or the factory.

Carefully unpack the unit. We recommend that you identify the items listed in the following table before discarding the packing material. If any items are missing or have been damaged during shipment, file a claim with the carrier immediately.

Item	Part Number	Quantity
N SYNC Cable	E30-7717-XX	1
Cushion	G13-2338-XX	1
Cushion	G13-2339-XX	4
Instruction Manual	B62-2283-XX	1

CONNECTION

Please consult your dealer for installing the network interface unit and repeater.




____2

Attach the KTI-3 to the repeater Accessory Cabinet using the supplied cushion.


There are two methods of attaching the KTI-3:

- 1. Attach 4 cushions (G13-2339) on the 4 base corners of the KTI-3, and place it into the Accessory Cabinet.
- 2. Attach the cushion (G13-2338) to the base of the KTI-3, and attach it to the Accessory Cabinet.



ORIENTATION

Rear Panel



- 1 DC Power supply connector Connect to Repeater.
- ② N SYNC jack Connect to Repeater.

3

③ LAN jack

Connect to Ethernet. Use a shielded, Category 5e or higher standard LAN cable shorter than 3 meters.

4 AUX jack

This jack is currently not used.

Indicators

4

Indicator	Color	Meaning
PWR	Green	Lights while the power is ON.
STATUS	Orange	Lights when used as a Host repeater.
LAN : Right (Full Duplex)	Green	Lights when in Full Duplex mode. Blinks when a collision status is detected in half Duplex mode.
LAN : Left (100Mbps)	Green	Lights when in 100Base-TX mode.