

Desk Microphone with Goose Neck

DESCRIPTION

- > Base station desk microphone with goose neck.
- > Attractive design.
- > High-sensitivity electret cartridge with amplifier.
- > PTT switch.
- > Special command board switching arrangements may be quoted upon request.
- > Voltage supply 9–15 VDC when connected as shown in the diagram below.
- > Supplied with 2 m cable.
- > Wind cap.



ORDERING

Type	Product No.
DM 6500 F/P	270000039

SPECIFICATIONS

Electrical	
Model	DM 6500 F/P
Type	Goose neck microphone
Pattern Type	Uni-directional
Impedance	Approx. 1 k Ω
Frequency Response	Shown in diagram below
Power Supply	Nominal: 2 V (Max. 10 V) directly on cartridge
Current Consumption	Approx. 0.5 mA
Sensitivity	-44 dB +/- 3 dB at 1 kHz rel. 1 V/Pa
Mechanical	
Cartridge Type	Electret
Materials	Brass and steel, epoxy laquered. Impact-proof plastic
Cable	2 m 5-wire with shield
Dimensions	400 (typ. H) x 108 (W) x 145 (D) mm
Weight	0.95 kg / 2.09 lb
Environmental	
Operating Temperature Range	Operating : -25° C to + 55° C Storage : -40° C to + 55° C

ADDITIONAL DATA

DM 6500 F/P

